

H SERIES

Lever and Push Operation Type Switch Tact Switch



Features

- The control unit provides both momentary operation by lever and center push operation.
- Using a single knob enables compound actions with simple operations.
- Reflow solderable.

Applications

- For the operation of telecommunication equipment such as mobile phones, etc.
- Compact, portable units such as camcoders, portable audios, car radios, etc.

Specification

Items		Standard
Operating temperature range		-30°C to +85°C
Electrical performance	Rating	10mA, 5V DC
	Output voltage	1V max. at 1mA 5V DC
	Contact resistance	100mW max.
	Lifetime	100,000 Cycles
Durability	Operating force	Lever portion 70 ± 40gf Push portion 200 ± 100gf
Mechanical performance	Travel	4-direction -25° -0° - +25°
		Push portion 0.85 ± 0.1mm

Diagram

No.	Dimensions	Circuit Diagram																																				
		Pad Layout																																				
1	<p>• TMHU28</p> <p>• TMHU29</p> <p>Code table</p> <table border="1"> <thead> <tr> <th>Angle</th> <th>25°</th> <th>CW</th> <th>0°</th> <th>CCW</th> <th>25°</th> </tr> </thead> <tbody> <tr> <td>Terminal ①</td> <td>(21.5°)</td> <td>(11°)</td> <td></td> <td></td> <td></td> </tr> <tr> <td>Terminal ②</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Terminal ③</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Terminal ④</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> <tr> <td>Terminal ⑤</td> <td></td> <td></td> <td></td> <td></td> <td></td> </tr> </tbody> </table>	Angle	25°	CW	0°	CCW	25°	Terminal ①	(21.5°)	(11°)				Terminal ②						Terminal ③						Terminal ④						Terminal ⑤						
Angle	25°	CW	0°	CCW	25°																																	
Terminal ①	(21.5°)	(11°)																																				
Terminal ②																																						
Terminal ③																																						
Terminal ④																																						
Terminal ⑤																																						

MULTI-FUNCTION SWITCH