

|   |                     |          |       |       |       |      |         |
|---|---------------------|----------|-------|-------|-------|------|---------|
| 阻值范围<br>Resistance range                          | 500Ω TO 1MΩ         |          |       |       |       |      |         |
| 阻值允许误差<br>Tolerance of resistance                 | ± 20%               |          |       |       |       |      |         |
| 电值规律<br>Resistance(law) taper                     | ABCDW               |          |       |       |       |      |         |
| 额定功率<br>Power Rating                              | 规律Taper \ 行程Travel  |          | 10mm  | 15mm  | 20mm  | 30mm | 45-60mm |
|   | 直线<br>B             | 双联Single | 0.05  | 0.05  | 0.1   | 0.2  | 0.25    |
|   |                     | 单联Dual   | 0.025 | 0.025 | 0.05  | 0.1  | 0.125   |
|   | 其它<br>Except B      | 双联Single | 0.025 | 0.025 | 0.5   | 0.1  | 0.125   |
|   |                     | 单联Dual   | 0.012 | 0.012 | 0.025 | 0.05 | 0.05    |
| 额定电压<br>Rated voltage                             | 直线 B                |          | 100   | 100   | 200   | 200  | 200     |
|   | 其它Except B          |          | 50    | 50    | 150   | 150  | 150     |
| 绝缘电阻<br>Insulation resistance                     | 10MΩ Min AT 250V DC |          |       |       |       |      |         |
| 耐电压<br>Withstanding Voltage                       | 1Min,AT 250V AC     |          |       |       |       |      |         |
| 动作力<br>Operating force                            | 10~120gf.cm         |          |       |       |       |      |         |
| 定位点起动力<br>Click slip-out force(only center click) | +20~150gf.cm        |          |       |       |       |      |         |
| 滑动寿命<br>Sliding life                              | 10,000 Cycles       |          |       |       |       |      |         |

