## A SERIES







# 3.2x4.2 Miniature Type Compact High Operting Force Tact Switch



#### HOW TO ORDER A Package Style B=Bulk R=Reel Serial Number 10=U type **Operating Force** B=180gf 11=Flat Termination Type C=250gf Switch Height U=U type H=400gf 025=2.5mm F=Flat

#### **Features**

- Its compact size contributes to make application units to be smaller and lighter.
- Large stem top surface. Excellence in operationality and mountability.
- Packaged with a 12mm wide embossed taping.

### **Applications**

- Car audio, car navigation systems, Keyless entry systems
- For operating various electronic devices such as audio devices, automotive units, communication devices, measuring instruments, etc.

#### Specification

Items Operating temperature range		Standard -30°C to +85°C	
Insulation resistance	100MWmin. 100V DC		
Dielectric strength	250V AC for 1 min.		
Contact resistance	500mWmax.		
Durability	Lifetime	100,000 Cycles min.	
Mechanical performance	Operating force	B:180gf C:250gf H:400gf	
	Travel	0.20 ± 0.1mm	

### Diagram

No.	Dimensions	Circuit Diagram Pad Layout
1	TVAU10	① ② ② ③ ④ ② ③ ② ② ② ② ② ③ ③ ② ② ② ② ③ ② ② ② ②
2	• TVAF11	3 4 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8 8