



| 项目Items | 型号Type 指标Index | WH148-1AK | WH160AK/WH166 | WH148-K | RV17 | WH168 | WH116AK | WH138 |
|--------------------------------------|-------------------|-----------------|-----------------|-----------------|-----------------|-----------------|------------------|-----------------|
| 总机械旋转角 Total rotation angle | | 300° | 300° | 300° | 260° | 300° | 270° | 300° |
| 动作力 Operating force | | 20~200gf.cm | 20~200gf.cm | 20~200gf.cm | 20~200gf.cm | 20~200gf.cm | 20~200gf.cm | 20~200gf.cm |
| 止挡强度 Shaft Stopper Strength | | 6Kgf.cm/min | 3Kgf.cm/min | 4Kgf.cm/min | 3Kgf.cm/min | 5Kgf.cm/min | 3Kgf.cm/min | 6Kgf.cm/min |
| 开关动作角度 Switch working angle | | 35±5° | 35±5° | 35±5° | 30±10° | 40±10° | 3mm | 50±10° |
| 开关操作力 Switch working torque/force | | 50~300gf.cm | 50~300gf.cm | 50~400gf.cm | 50~300gf.cm | 50~300gf.cm | 200~max | 150~450gf.cm |
| 额定功率 power Rating | | 0.125W 0.06W | 0.125W 0.06W | 0.125W 0.06W | 0.125W 0.06W | 0.125W 0.06W | 0.125W 0.06W | 0.2W 0.1W |
| 额定电压 Rated voltage | | 200V 150V | 200V 150V | 200V 150V | 200V 150V | 200V 150V | 200V 150V | 500V 250V |
| 绝缘电阻 Insulation resistance | | DC500v 100MΩ | DC500v 100M | DC500v 100MΩ | DC500v 50MΩ | DC500v 100MΩ | DC500v 100MΩ | DC500v 100MΩ |
| 耐电压 Withstanding Voltage | | AC500V, 1minute | AC500V, 1minute | AC500V, 1minute | AC500V, 1minute | AC500V, 1minute | AC1000V, 1minute | AC500V, 1minute |
| 开关接触电阻 Switch contact resistance | | less than 20mΩ | less than 20mΩ | less than 20mΩ | less than 20mΩ | less than 20mΩ | less than 20mΩ | less than 20mΩ |
| 开关额定功率 Switch ratings | | 16VDC 3A | 12VDC 1A | 16VDC 3A | 12VDC 1A | 125VDC 3A | 250VDC 2A | 125VDC 1A |
| 机械耐久性 Mechanical endurance | | 10000 cycles | 10000 cycles | 10000 cycles | 10000 cycles | 10000 cycles | 10000 cycles | 10000 cycles |
| 开关寿命 Switch life | | 10000 times | 10000 times | 10000 times | 10000 times | 10000 times | 25000 times | 10000 times |