



B SERIES

2.5x7.0 SMT & Right Angle Tact Switch



HOW TO ORDER



Features

- Horizontal type capable of operating in the horizontal direction to the PC board.
- Reflow solderable.
- Packaged with a 16mm wide embossed taping.

Applications

- Various portable electronic devices
- For operating various compact electronic devices such as mobile phones and communication devices, that require high density mounting
- For operating various MP4, MP3.

Specification

Items		Standard
Operating temperature range		-30°C to +85°C
Electrical performance	Rating	50mA, 12V DC
	Insulation resistance	100M Ω min. 100V DC
	Dielectric strength	250V AC for 1 min.
	Contact resistance	100m Ω max.
Durability	Lifetime	J:D:E:B:50,000Cycles C:G:30,000 Cycles
Mechanical performance	Operating force	B:180gf C:250gf D:70gf E:130gf J:160gf G:320gf
	Travel	0.25 \pm 0.1mm

Diagram

No.	Dimensions	Circuit Diagram Pad Layout			
1	<p>• THBM02</p> <table border="1"> <tr> <td>A</td> </tr> <tr> <td>r0.6</td> </tr> <tr> <td>r0.8</td> </tr> </table>	A	r0.6	r0.8	
A					
r0.6					
r0.8					
2	<p>• THBM03</p>				