

| 型号 Type 项目 Items | WX110 | WX112 | WX118 | WXD3590 | WXD534 | WXD3-13 | WX14 |
|-----------------------------------|-------------|-------------|-------------|---------------------|---------------------|---------------------|---------------------|
| 阻值范围 Resistance range | 22Ω~10kΩ | 22Ω~47kΩ | 100Ω~20kΩ | 200Ω~100kΩ | 200Ω~100kΩ | 100Ω~56kΩ | 27Ω~22kΩ |
| 阻值允许误差 Tolerance of resistance | ±5% ±10% | ±5% ±10% | ±5% | ±5% | ±5% | ±5% | ±5% ±10% |
| 总机械行程 Total mechanical travel | 300±10° | 300±10° | 285±5° | 3600±10° | 3600±10° | 3600±20° | 300±10° |
| 起动力矩 Operating force | 3.5~100mN.m | 3.5~100mN.m | 3.5~100mN.m | 3.5~100mN.m | 3.5~100mN.m | 3.5~100mN.m | 3.5~100mN.m |
| 额定电压 Rated voltage | 100V | 320V | 200V | 160V | 160V | 160V | 200V |
| 额定功率 Power Rating | 1W | 5W | 1W(40℃) | 2W(55℃) 0W(125℃) | 2W(55℃) 0W(125℃) | 2W(55℃) 0W(100℃) | 3W(85℃) 0W(125℃) |

