
# **I SERIES**

# 6.0x6.0 Led Built-in Type









#### **Features**

- Snap-in type, which can be directly mounted on PC board.
- Some of output terminals can be also used as jumper leads, thus making circuit design easy.
- Standard knobs are available.

### **Applications**

 Operating switches in all types of electronic equipment such as audio apparatus, office equipment, communications apparatus, measuring instruments, TV sets, VCRs, etc

## Specification

Items Operating temperature range		Standard -25°C to +85°C	
Insulation resistance	100MWmin. 100V DC		
Dielectric strength	250V AC for 1 min.		
Contact resistance	100mWmax.		
Durability	Lifetime	100,000 Cycles Min	
Mechanical performance	Operating force	J:160gf B:180gf C:250gf	
	Travel	0.25 ± 0.1mm	

## Diagram

No.	D	Circuit Diagram Pad Layout	
1	• LS613  • RESET • • • • • • • • • • • • • • • • • • •	7.5 7.5 7.5 7.5 7.5 9 9 9 9 9 9 9 9 9 9 9 9 9	(5) (6) (6) (7) (6) (7) (7) (7) (7) (7) (7) (7) (7) (7) (7
2	• LS614	7.5 7.5 7.5 7.5 7.5 7.5 7.5 7.5	© 2 6 3 4 LED 18

