

# VC2 Series

## 2.5\*2.0 mm SMD VCTCXO

### FEATURE

- Typical 2.5 x 2.0 x 0.75 mm ceramic SMD package
- For automatic assembly
- Compactness and light weight
- VCTCXO available
- Low thickness

### TYPICAL APPLICATION


- GPS
- WiMAX, WLAN
- Mobile Phone



RoHS Compliant Standard

### DIMENSION (mm)

### SOLDER PAD LAYOUT (mm)



### ELECTRICAL SPECIFICATION

Parameter	2.8V		2.5V		1.8V		Unit
	Min.	Max.	Min.	Max.	Min.	Max.	
Supply Voltage Variation (VDD) 5%	2.66	2.94	2.375	2.625	1.71	1.89	V
Frequency Range	13	52	13	52	13	52	MHz
Standard Frequency	16.367667, 16.368, 16.369, 19.2, 19.68, 20, 26, 40						
Frequency Tolerance*	-	±2.0	-	±2.0	-	±2.0	ppm
Frequency Stability							
Vs Supply Voltage (±5%) change	-	±0.2	-	±0.2	-	±0.2	ppm
Vs Load (±10%) change	-	±0.2	-	±0.2	-	±0.2	ppm
Vs Aging	-	±1.0	-	±1.0	-	±1.0	ppm/year
Supply Current 13 MHz ≤ F0 < 26 MHz	-	2.0	-	2.0	-	2.0	mA
26 MHz ≤ F0 ≤ 52 MHz	-	2.5	-	2.5	-	2.5	mA
Output Level (Clipped Sine Wave)	0.8	-	0.8	-	0.8	-	Vp-p
Load	10KΩ/10pF		10KΩ/10pF		10KΩ/10pF		
Control Voltage Range (VCTCXO)	0.4	2.4	0.4	2.4	0.3	1.5	V
Pulling Range (VCTCXO)	±5.0	-	±5.0	-	±5.0	-	ppm
Vc Input Impedance (VCTCXO)	500	-	500	-	500	-	KΩ
Phase Noise @ 19.2 MHz							
100 Hz	-115		-115		-115		dBc/Hz
1 KHz	-135		-135		-135		
10 KHz	-148		-148		-148		
Start Time	-	2	-	2	-	2	mSec
Storage Temp. Range	-55	125	-55	125	-55	125	°C

Standard frequencies are frequencies which the crystal has been designed and does not imply a stock position

\*Frequency at 25°C, 1 hour after reflow

Packing: Tape & Reel 3000 pcs per Reel

### FREQ. STABILITY vs. TEMP. RANGE

Temp. (°C)	ppm	±0.5	±1.0	±1.5	±2.0	±2.5
		0~+55	○	○	○	○
-10~+60	○	○	○	○	○	
-20~+70	○	○	○	○	○	
-30~+85	△	○	○	○	○	
-40~+85	△	△	○	○	○	

\* O: Available    △: Conditional    X: Not available