

Series WX3

SMD PACKAGE FOR TUNING FORK 32.768KHz

FEATURE

- Wide Frequency range
- Small size
- Tape & Reel
- Reflow available



APPLICATIONS

- Microprocessor Systems
- Consumer Electronics




ELECTRICAL SPECIFICATIONS

Frequency	32.768KHz
Frequency Tolerance (at 25°C)	±20ppm
ESR	50Kohm Max
Turnover Temperature	25 ± 5°C
Frequency Temperature Curve	-0.034(±0.006)ppm/°C ²
Storage Temperature Range	-55 °C to +125 °C
Operable Temperature Range	-40 °C to + 85 °C
Shunt Capacitance (C0)	1.3pF Typ
Dynamic Capacitance (C1)	2.4fF Typ
Driver Level (Typical)	1 µW Max
Load Capacitance(C _L)	6.0pF
Aging @25°C 1 st year (Max)	±3ppm/year

REMARK: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE. PLEASE CONFIRM WITH OUR SALES ENGINEER.

Frequency VS Temperature Curve




PACKING AND DIMENSIONS


Dimensions (Unit: mm)

Series WX3

SMD PACKAGE FOR TUNING FORK 32.768KHz



Reflow Soldering Profile



Series WX3

SMD PACKAGE FOR TUNING FORK 32.768KHz

Packing (Tape & Reel)

