

300mA、8V、Low Power LDO

CYP6216

General Description

CYP6216 series are a highly precise, lower consumption, 3 terminal, positive voltage regulators manufactured using CMOS and laser trimming technologies. The series provides large currents with a significantly small dropout voltage .

The CYP6216 consists of a current limiter circuit, a driver transistor, a precision reference voltage and an error correction circuit. The series is compatible with low ESR ceramic capacitors. The current limiter's foldback circuit operates as a short circuit protection as well as the output current limiter for the output pin. Output voltages are internally by laser trimming technologies. It is selectable in 0.1V increments within a range of 1.5V to 3.6V. CYP6216 series are available in SOT-23,SOT23-3 and SOT89 packages.



Features

- Low power consumption
- Low voltage drop
- Low temperature coefficient
- Low Quiescent Current: 5 μ A @ 6V
- Output voltage accuracy: tolerance $\pm 2\%$

Applications

- Battery-powered equipment
- Reference voltage sources
- Cameras,video cameras
- Portable AV systems
- Mobile phones
- Portable games

Order information

Device	Package	Packaging style	SPQ
CYP6216-XXNX	SOT23	Reel	3000
CYP6216-XXMX	SOT23-3	Reel	3000
CYP6216-XXPX	SOT89	Reel	1000

Order Information

CYP6216-①②③④

Designator	Symbol	Description
①②	Integer	Output Voltage(1.5V~3.6V)
③	N	Package:SOT23
	M	Package:SOT23-3
	P	Package:SOT89
④	R	RoHS / Pb Free
	G	Halogen Free


Note: "①②" stands for output voltages. Other voltages can be specially customized.

Marking Rule


Part No	Marking			
	(1)	(2)	(3)	(4)
CYP6216-15YR	6	5	E	9
CYP6216-18YR	6	5	K	5
CYP6216-25YR	6	5	T	5
CYP6216-28YR	6	4	F	K
CYP6216-30YR	6	5	Z	5
CYP6216-33YR	6	6	2	K
CYP6216-36YR	6	6	5	K

Note: Y: Representative product packaging


Block Diagram



Pin Assignment



Typical Application



Absolute Maximum Ratings

Parameter	Symbol	Ratings	Units
Input Voltage	V _{IN}	8	V
Output Current	I _{OUT}	300*	mA
Output Voltage	V _{OUT}	V _{SS} -0.3~V _{IN} +0.3	V
Power Dissipation	P _d	0.20	W
		0.25	W
		0.50	W
Operating Temperature Range	T _{opr}	-40~+85	°C
Storage Temperature Range	T _{stg}	-55~+125	°C

* I_{OUT}=P_d/(V_{IN}-V_{OUT})

Electrical Characteristics

CYP6216 for any output voltage

(Ta=25°C)


Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
Output Voltage	Vout	Vin=Vout+1V 1.0mA≤Iout≤30mA	Vout×0.98	--	Vout×1.02	V
Output Current	Iout	Vin-Vout=1V	--	300	--	mA
Low dropout	Vdrop	Refer to the next table				
Line Regulation	△ Vout/△ Vin*Vout	1.6V≤Vin≤8V Iout=40mA	--	0.1	0.2	%/V
Load Regulation	△ Vout /△Iout	Vin= Vout+1V 1.0mA≤Iout≤80mA	--	12	30	mV
Output voltage Temperature Coefficiency	△ Vout/(Ta -Vout)	Iout=30mA 0°C≤Ta≤70°C	--	±100	--	ppm/ °C
Supply Current	Iss1	--	--	5	10	μA
Input Voltage	Vin	--	--	6	8	V
PSRR	PSRR	F=1KHz Vin=Vout+1V	--	50	--	dB

Electrical Characteristics by Output Voltage:


Output Voltage Vout(V)	Dropout Voltage Vdif (V)		
	Conditions	Typ.	Max.
Vout≤1.5V	Iout=100 mA	0.5	0.68
1.8 ≤ Vout ≤ 2		0.39	0.53
2.8 ≤ Vout ≤ 5.0		0.23	0.39

Typical Performance Characteristics


Test Conditions:CYP621630NR CIN=1 μ F, COUT=1 μ F,T_a=25°C,unless otherwise indicated.




V_{OUT} Vs Output Current
CYP6216-30NR



V_{OUT} Vs Input Voltage
CYP6216-
30NR




V_{OUT} vs Temperature
CYP6216-30NR




V_{OUT} vs Temperature
CYP6216-
30NR

Typical Performance Characteristics


Test Conditions:CYP621630NR Vin=Vout+2V,CIN=1μF, COUT=1μF,T_a=25°C,unless otherwise indicated.




Power-Up at Vout=3.0V Time(250μs/div)
(Vin=5V,Iout=1mA)



Power-Up at Vout=3.0V Time(250μs/div)
(Vin=5V,Iout=100mA)




Input Voltage transient response
(Vout=3.0V,Iout=1mA)




Input Voltage transient response
(Vout=3.0V,Iout=100mA)

Package Information

3-pin SOT23 Outline Dimensions




Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	0.900	1.150	0.035	0.045
A1	0.000	0.100	0.000	0.004
A2	0.900	1.050	0.035	0.041
b	0.300	0.500	0.012	0.020
c	0.080	0.150	0.003	0.006
D	2.800	3.000	0.110	0.118
E	1.200	1.400	0.047	0.055
E1	2.250	2.550	0.089	0.100
e	0.950 TYP.		0.037 TYP.	
e1	1.800	2.000	0.071	0.079
L	0.550 REF.		0.022 REF.	
L1	0.300	0.500	0.012	0.020
θ	0°	8°	0°	8°

3-pin SOT23-3 Outline Dimensions


Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min	Max	Min	Max
A	1.050	1.250	0.041	0.049
A1	0.000	0.100	0.000	0.004
A2	1.050	1.150	0.041	0.045
b	0.300	0.500	0.012	0.020
c	0.100	0.200	0.004	0.008
D	2.820	3.020	0.111	0.119
E	1.500	1.700	0.059	0.067
E1	2.650	2.950	0.104	0.116
e	0.950(BSC)		0.037(BSC)	
e1	1.800	2.000	0.071	0.079
L	0.300	0.600	0.012	0.024
θ	0°	8°	0°	8°

3-pin SOT89 Outline Dimensions



Symbol	Dimensions In Millimeters		Dimensions In Inches	
	Min.	Max.	Min.	Max.
A	1.400	1.600	0.055	0.063
b	0.320	0.520	0.013	0.020
b1	0.400	0.580	0.016	0.023
c	0.350	0.440	0.014	0.017
D	4.400	4.600	0.173	0.181
D1	1.550 REF.		0.061 REF.	
E	2.300	2.600	0.091	0.102
E1	3.940	4.250	0.155	0.167
e	1.500 TYP.		0.060 TYP.	
e1	3.000 TYP.		0.118 TYP.	
L	0.900	1.200	0.035	0.047



CYP6216

Special Version

The company reserves the right of final interpretation of this specification.

Version Change Description

Versions: V1.0

Writer: Xin CHun Li

Time: 2022.10.15

Amendant record:

1. Original Version